



NPR72GR-5JXA(カスタム) 標準カラー:アーチホワイト

# ISUZU

## NPR72GR – 5JXA

### 4 X 2 TRUCK

GVM	GCM	TARE WEIGHT	NOMINAL PAYLOAD	WHEELBASE	SHORT CODE
5815kg	TBC	2650kg	3000kg	2765mm	NP 12

#### ENGINE

Model: 4HJ1  
 Type: 4 cylinder in line  
 OHC direct injection diesel  
 Bore x Stroke: 115mm x 120mm  
 Displacement: 4985cc  
 Compression Ratio: 19.5:1  
 Power Output: 150 PS @ 3100rpm  
 Torque: 363 Nm @ 1600rpm

#### FRONT AXLE/SUSPENSION

Capacity: TBA  
 Semi elliptical, alloy steel, tapered multi leaf springs. Hydraulic double acting, telescopic shock absorbers  
 \*Axle load restricted to 2570kg by tyres

#### CAB AXLE/SUSPENSION

Forward control all steel tilt cab  
 Liquid infusion cab suspension  
 Large "Aero" Type rear view mirrors  
 L/H electric rear view mirror  
 90 degree wide opening doors  
 Large aluminum inner door steps  
 Cab finished in "Arc White"

#### STEERING

Engine sensitive power steering  
 Tilt: and telescopic adjustable

#### TRANSMISSION

Model: MXA6R  
 6 spd overdrive, synchromesh with with short-throw drop type floor mounted gearshift. Gear Ratios: 1  
 1<sup>st</sup> 4.987  
 2<sup>nd</sup> 2.870  
 3<sup>rd</sup> 1.594  
 4<sup>th</sup> 1.000  
 5<sup>th</sup> 0.728  
 6<sup>th</sup> 0.626  
 Reverse 4.774

#### WHEELS & TYRES

One piece 16in rim – 5 stud  
 215/80R16 tubeless radials  
 Single front – dual rear

#### BRAKES

Hydraulic dual circuit vacuum assisted  
 Front two leading shoes  
 Rear dual two leading shoes  
 Transmission mounted internal expanding park brake.  
 Auxiliary exhaust brake  
 HSA – Hill Start Assist

#### STANDARD EQUIPMENT

Heavy duty cloth high back seats  
 Air conditioning  
 Central Locking  
 Power Windows  
 Key reminder buzzer  
 AM/FM radio twin speakers & alarm  
 Drivers side door step light  
 Passenger & center seat back tray  
 Back panel tray  
 Side intrusion beams  
 3 point ELR L & R side seatbelts  
 Drivers seatbelt reminder light  
 Locking fuel cap  
 Drop side rear body  
 Fog lamps  
 Sliding drawer cup holder

#### REAR AXLE/SUSPENSION

Ratio: 5.571:1 Capacity: TBA  
 Semi elliptical, alloy steel, tapered multi leaf springs  
 Hydraulic double acting, telescopic shock absorbers  
 \* Axle load restricted to 4860 kg by tyres

#### ELECTRICAL

24 Volt 50 amp alternator  
 Batteries: 2 x 75D23R in line

#### WARRANTY

Vehicle, powertrain & corrosion warranty: 12 months or 100, 000km (whichever comes first).

#### 150PS 4HJ1

